


Acme Rolling Grilles

GRILLE SELECTION CHART


OPERATION	ACME TYPE	MOUNTING	SELECTION FEATURES
PUSH-UP (manual)	GFM	Interior face of wall	Aluminum grilles limited to 16 feet wide and 10 feet high. Steel grilles limited to 10 feet wide and 10 feet high. Simple and rapid operation. Min. clearance required.
	GJM	Between jambs interior (apply when clearances are insufficient for face of wall)	
CHAIN	GFC	Interior face of wall	For grilles up to 20 feet wide and 14 feet high. Rapid operation chain pull maximum 35 pounds, smooth reduction gearing.
	GJC	Between jambs interior (apply when clearances are insufficient for face of wall)	
CRANK	GFCR	Interior face of wall	Awning type crank with removable arm (standard). Wall mounted crank with removable crank handle (optional).
	GJCR	Between jambs interior (apply when clearances are insufficient for face of wall)	
MOTOR	GFM0	Interior face of wall	For grilles up to 45 feet wide Rapid and versatile operation Remote control
	GJM0	Between jambs interior (apply when clearances are insufficient for face of wall)	

NOTE: For Aluminum, use prefix A. For Stainless Steel, use prefix SS.



TYPE G1

Standard pattern with vertical links 9" on center, horizontal spacing 1 1/2" on center. Also available with links spaced 6", 4" and 3" on center for greater security.



TYPE G2

Brick pattern with staggered links. Both can be furnished in steel and aluminum with a variety of finishes.

DETAILS AND CLEARANCE DIMENSIONS

